



PIN	SYMBOL	PIN	SYMBOL
1	NC	21	NC
2	NC	22	LEDA
3	NC	23	GND
4	NC	24	VCC
5	NC	25	VSYNC
6	NC	26	HSYNC
7	NC	27	DOTCLK
8	NC	28	GND
9	NC	29	GND
10	VGL	30	DB00
11	VGH	31	DB01
12	GND	32	DB02
13	NC	33	DB03
14	AVDD	34	DB04
15	NC	35	DB05
16	NC	36	SDA
17	NC	37	SCL
18	NC	38	CS
19	LEDK	39	NC
20	NC	40	RESET

Specification:

- (1). Viewing angle: ANY
- (2). Display mode: 262K TFT/Normally White/Transmissive
- (3). Operating temp.: -20°C~+70°C
Storage temp.: -30°C~+80°C
- (4). IC: IL9342C
- (5). Backlight: 10 chip White LED ,in Parallel Vr:31 V If:20 mA
- (6). Dimensions with mark "*" are important, with mark "()" are referenced
- (7). Request ROHS

		深圳市顺世科技有限公司	
SHENZHEN SUNNY TECHNOLOGY CO., LTD			
DRAWN BY:	2019.03.12	ST020C-LCM-V1.0	
CHECK BY:		SCALE: 1:1	
APPROVER:		UNIT: mm	TOLERANCE: ±0.2
		PAGE: 1 of 1	MATERIAL