



[Home](#)

[About Us](#)

[Products](#)

[News](#)

[R&D](#)

[Contact](#)



Language

[e](#)

[Us](#)

[European terminal blocks](#)

[Shrapnel terminal](#)

[Barrier terminal](#)

[High current fence type terminal](#)

[Plug-in terminal](#)

[Through-wall terminal](#)

[Front and rear through-type terminals](#)

[Up and down through-type terminal](#)

[blocks](#)

[Rail terminal](#)

[Accessories](#)

[Plastic shell parts](#)

[All categories >](#)

[European terminal blocks](#) >

[Shrapnel terminal](#) >

[Barrier terminal](#) >

[High current fence type terminal](#) >

[Plug-in terminal](#) >

[Through-wall terminal](#)

[Front and rear through-type](#)

[terminals](#)



3.81mm(300V,10A)

Product Number TJ381-11

技术参数Parameter:

UL技术 参数 UL Technical Data	B	C	D
额定电压/电流 Rated Voltage / Current V/A	300/10		
压线范围 Wire Range AWG	16-24		
IEC技术参数 IEC Technical Data			
过电压等级 Overvoltage Category	Ⅲ	Ⅲ	Ⅱ
污染等级 Contamination Class	3	2	2
额定电压/电流 Rated Voltage / Current V/A	160 / 10	160 / 10	160 / 10
冲击电压 Rated Surge Voltage KV	2.5	2.5	2.5
接线截面积 Rated Connecting Capacity mm2	1.0	1.0	1.0
材料Material			
绝缘材料/阻燃等级 Insulation Material / Inflammability Class	PA66 / UL94, V-0		





[Accessories](#)

[Plastic shell parts](#)

其它信息 Other Data	
PCB板孔径 PCB Hole Diameter mm	φ1.2
剥线长度 Stripping Length mm	4-5
螺钉/扭力 Screw / Torque /lbf.in	M2 / 1.8-2.0

Messages

If you have any good suggestions and opinions on our company, or want to consult our products, please fill in the form below, and we will contact you as soon as possible!

Name

Mobile

E-mail

Message

SUBMIT

About Us

- Company Profile
- Qualification
- Company Culture
- Sales System
- Products

- European terminal blocks
- Shrapnel terminal
- Barrier terminal
- High current fence type terminal



Please enter the required content





[Home](#)

[About Us](#)

[Products](#)

[News](#)

[R&D](#)

[Contact](#)



Language

[e](#)

[Us](#)

Plastic shell parts
Download Center
News

Company News
Industry News



online consultation

